

Amendments to the Claims:

The following listing of the claims replaces and supersedes all previous listings.

1. (Previously Presented) Method for producing a layer compound (6) with at least two security features disposed in register to each other, comprising the following steps:

- providing a first carrier foil (100) with at least one first security feature and first register marks,
- providing a second carrier foil (200) with at least one second security feature and second register marks,
- joining the first carrier foil to the second carrier foil, at least one of the two carrier foils being under tensile stress and at least one of the second or the first carrier foil being controlled in longitudinal direction and transverse direction with the help of the first and second register marks in such a way, that a layer compound is the result, in which the first and second security features are disposed in register to each other, whereas the controlling of at least one of the second carrier foil (200) or the first carrier foil (100) is effected by stretching the carrier foil in longitudinal direction of the carrier foil.

2. (Cancelled)

3. (Previously Presented) Method according to claim 1, characterized in that the second carrier foil (200) is shorter than the first carrier foil (100) and is stretched relative to the first carrier foil (100).

4. (Previously Presented) Method according to claim 1, characterized in that the first carrier foil (100) due to the tensile stress undergoes a constant stretching in longitudinal direction of the carrier foil and the second carrier foil (200) is stretched relative to the stretching of first carrier foil (100).

5. (Previously Presented) Method according to claim 1, characterized in that the carrier foils (100, 200) are provided on rollers (3, 4) and are drawn off the rollers, the stretching of at least one of the first &or second carrier foil (100 or 200) in longitudinal direction of the carrier foil being achieved by a controlled slow down of this roller when drawing off the carrier foil from the respective roller.

6. (Currently Amended) Method according to claim 1, characterized in that an ~~an~~ exactly a registered joining of the two carrier foils (100, 200) with respect to their longitudinal edges is achieved by means of a tension group (11).

7. (Original) Method according to claim 6, characterized in that the tension group is controlled with the help of the first and second register marks.

8. (Previously Presented) Method according to claim 1, characterized in that the register marks are read by means of light guides or CCD-cameras.

9. (Previously Presented) Method according claim 1, characterized in that the security features are used as register marks.

10. (Previously Presented) Method according to claim 1, characterized in that the layer compound is divided into so-called endless threads or endless strips.

11. (Previously Presented) Method for producing a security element comprising the procedure steps according to claim 1, characterized in that from the layer compound (6) a security element with its final transverse and longitudinal dimensions is divided out.

12. (Currently Amended) Layer compound (6) produced by the method according to claim 1 or 11, comprising two carrier foils (100, 200) each having at least one security feature covering the respective carrier foil only partially, characterized in that ~~the two carrier foils are joined to each other in such a way, that the security features are disposed in register to each other.~~

13. (Cancelled)

14. (Original) Multilayer security element comprising a layer compound according to claim 12.

15. (Original) Multilayer security element according to claim 14, in the form of a thread, strip, label or tag.

16. (Previously Presented) Object to which a security element according to claim 14 is firmly joined by adhesive bonding, embedding, or attaching.

17. (Previously Presented) Document of value with an applied or embedded strip- or thread-shaped security element according to claim 15.

18. (Previously Presented) An object to which a security element according to claim 15 is firmly joined by adhesive bonding, embedding, or attaching.

19. (Previously Presented) The document of value of claim 17, comprising a bank note.